

Institute technical Summer Projects
2023

iKshana

Guiding steps, Empowering Journeys



Content

01

The Problem, Inspiration and Objective

02

What is iKshana?

03

How it works: Hardware, Software and User

04

Design process

05


Results

06

Future Goals

07

Our Team



The Problem

Several in a visually impaired person's life..



Navigation

One in around every eighty Indians are partially or completely blind, who require constant aid and face problems in even moving around in their own house, let alone streets and footpaths.



Cumbersome and inefficient solutions

Human/animal guides or smart sticks necessitate dependence on individuals/accessories. More sophisticated solutions are costly.



Walking shouldn't feel "Different"

Current solutions easily cause the user to be viewed as visually impaired, which creates segregation in something as simple as everyday commute and may even compromise their safety.

The Objective

What we're trying to accomplish..



A More Natural Solution

We hope to provide the same level of aid through a device which is more convenient than the other solutions available today.



Affordability

If our goal is to reach the most affected by limited vision, affordability is a high priority, which we draw from easily available components, modularity and integrating its use with your smartphone



Self-Confidence & Self sufficiency

We want to create a place where the visually impaired are as confident and self-sufficient as any other person, in this aspect at least.

What is iKshana?

As simple as an accessory

iKshana is a wearable harness with straps which you put on over your shoes and around your ankle.

Know your surroundings

iKshana is equipped with ultrasonic sensors to check for any obstacles in the user's path and around the user.


Large-scale navigation

It uses integration with the navigation capabilities of the phone to tell you where you can go. One major part of navigation we decided to address was navigating road intersections.

Haptic feedback

The mode of communication with the user is through vibrations both of the smartphone and coin motors, which is easy to get used to, are intuitive and feels as natural as walking is for any other person

How it works: Hardware



How it works: Software

Aim

To enable visually impaired people to grasp general directions of possible paths they can take at path intersections and provide more directional accuracy to their intuition, while keeping them aware of obstacles constantly

How it works: Software

1a

Made an app in Android Studio to obtain latitude and longitude of the person through the Fused Location Provider client API in Google Play Services.

2a

The API finds the user's location through nearby Wi-fi access points and GPS.

3b

This involves coordinates of road intersections, the number of branching roads, bearings of roads.

1b

Using Open street map, obtain data about the map geometry of the areas in and around IIT Bombay, in .OSM form

2b

Python code parses the data and builds a database specific information of path intersections using the Osmium library with geocoding functions.

How it works: Software

1c

The database of all intersections is uploaded to the app backend.

2c

Data about a particular intersection is accessed as the user nears that intersection.

3c

Identify the user's path, send data to the ESP-32 and help the user manoeuvre the junction through vibrational cues.

4b

Export this data in JSON format to the android app

ESP-32's Job

The ESP-32 code features an obstacle detection part and a part for intersection manoeuvring, which at any point is overridden by obstacle detection when needed. One ESP-32 on each foot bridge the sensors, actuators and smartphone. It receives instructions about the possible directions at an intersection from the Android app which is relayed to the user through vibrations.

How it works: User


1 The person's phone vibrates and the intensity of vibrations increase as the user nears an intersection.

2 A special signal like a blink denotes you've reached.



3 The program finds the road you're travelling along wrt the intersection using the JSON database in the app.

4 Vibration motors on the left and right iKshanas vibrate accordingly to indicate the direction that person can go.




Design Process

An overview



Ideation

Brainstorming, research
Approaching people,
thought experiments



Modelling

Program flow, soft
design, refinement,
sketching, research



Prototyping

Procuring materials,
Stitching, Wiring,
Programming,
SOLDERING



Testing T_T

Calibration, checking
the overall functions,
remodel.

Ideation




average angle for a normal foot, is around 21deg, so we can take it to be around 23-25 deg, for our

ER101
IoT and Mechatronics: An Introductory Overview
Highly recommended for ITSP teams

Tejal Barnwal Kalind Karia

4th July 08:00 PM Online

Kushal : 90300 20310 Teams Code : 6ebg5ku Anuj : 93592 12094



9:54 PM

Tap to return to m...

Post
ERC - Electronics a

Tejal Ashwini Barnwal


Yash B.
Could please give different types of batteries, coin cells, Li ion etc. and how to get batteries for custom voltage/power needs?

One way is you can connect multiple 3.7V lithium-ion batteries in series and get a case for it. You can get it procured with specialized vendors(like robu), but it's usually preferable to use standard batteries just because they are cost-effective, and easy to integrate if they satisfy your requirements.

Kyari Alpeshkumar Ponkiya 9:52 pm
the recording will be available for late reference

Reply



Picture	Model	Nominal Voltage(V)	Nominal capacity (mAh)	Dimensions		Average Weight(g)	Cross reference model		
				Diameter(mm)	Thickness(mm)				
	AG13	1.5	150	11.6	5.4	1.95	LR44	L1154	357A
	AG12	1.5	120	11.6	4.2	1.55	LR43	L1142	386A
	AG11	1.5	16	7.9	2.1	0.40	LR721	-	362A
	AG10	1.5	75	11.6	3.1	1.16	LR1130	L1131	389A
	AG9	1.5	48	9.5	3.6	0.87	LR45	L936	394A
	AG8	1.5	41	11.6	2.1	0.87	LR1120	L1121	391A
	AG7	1.5	40	9.5	2.7	0.65	LR927	-	395A
	AG6	1.5	26	9.5	2.1	0.54	LR920	-	371A
	AG5	1.5	45	7.9	5.4	0.94	LR754	-	393A
	AG4	1.5	17	6.8	2.6	0.34	LR626	-	377A
	AG3	1.5	38	7.9	3.6	0.64	LR41	L736	392A
	AG2	1.5	25	7.9	2.6	0.47	LR726	-	396A
	AG1	1.5	14	6.8	2.1	0.28	LR621	-	364A
	521A	1.5	10	5.8	2.1	0.23	LR63	-	379A




Ads by Google

Send feedback Why this ad?

Modelling



Prototyping




A modern office interior with wooden desks, chairs, and large potted plants. The word "RESULTS" is overlaid in white text. The office has a high ceiling with exposed concrete beams and pipes, and large windows on the left side. The floor is made of light-colored wood. There are several large potted plants, including a large one in the foreground and several smaller ones hanging from the ceiling. The overall atmosphere is bright and airy.

RESULTS






Results: Hardware



The mechanical designs we modelled went through some iterations with minor changes, but in the end we have successfully been able to make 2 iKshana harnesses. 4 3D-printed modules which hold our electronic components, are durable and are superglued to stitched pads on the modules.



The power source also changed from sets of 6 lithium coin cells to 9V Batteries



Results: Software

From code to coordination...

Inputs



Location of the user
obtained on UI




OpenStreetMap data of
intersections stored in the
app files in a usable form




Osmium library was used to
extract this intersection
info from the mapping data


Ikkku:
The android
app



HC-SR04 sends obstacle
detection signals



vibration motors indicate
when an obstacle is close, and
tell you about junction types



Communicates with
the app to receive and
use appropriate info

Check out the Github repo [here](#)

Near Future goals

In the near-future, our goals are more accuracy, longer-lasting hardware and battery-life, and a more natural feel.

Here's how we might achieve them:

- Using Lidar Sensors in place of Ultrasonic sensors.
- Using more durable materials, bettering the design so it is easy on our wiring and more comfortable.
- Thinking of better ways to use vibrational cues, and more vibration motors to increase freedom of movement.
- Incorporate stronger & lightweight (ideally) power sources into the iKshana modules

Far Future goals

Software

- Machine learning algorithms can be used to make our model more accurate for daily routine commute.
- We want to replace ultrasonic sensors with cameras and state-of-the-art computer vision algorithms to make our product more accurate and safer, and more suited to smaller scales, where GPS may not work. One drawback is that this will be expensive.

Mechanical & Electrical

- We want to work on the power supply front. We plan to use piezoelectric motors coupled with batteries to charge them from the user's motion.
- Design PCBs and get them manufactured to have more reliable electronics.


One Critical Problem



The accuracy of our app in calculating relevant coordinates is limited because of disparities in the OpenStreetMap (open-source) data that we are using

Access to better map geometry data which may be under license might help us

Our Team



Abhineet
Agarwal



Chinmay
Moorjani



Yash Bhake



Tanish
Raghute